

WELL WATER TREATMENT SYSTEMS

Discount Water Supply Inc. est 2003
Water Treatment Systems, Parts, Supplies



1249 W. Airport Blvd. Sanford, FL. 32773
407-323-9010 1-877-753-4140

www.discountwatersupply.com

Water Analysis service is available in the store.

THIS BROCHURE DESCRIBES THE MODEL
133210 AND THE MODEL **134815** SYSTEMS.

Treatment Method: Chlorine Disinfection,
Carbon Filter and Softener.

Treatment Purpose: Domestic and light
commercial potable water only. Disinfection to
kill bacteria, removal of hydrogen sulfide, iron,
iron bacteria, manganese, calcium hardness.

The system includes these components

Flow switch, regulate the chlorine pump by
water usage. (not shown in picture)

Chlorine solution pump, 115 volt

Chlorine solution tank, 35 gallon.

Retention tank, 120 gallon fiberglass, Vacuum
relief valve included.

Filter, automatic backwash carbon filter with
NSF approved granular activated carbon.

Softener, automatic backwash with high
capacity ion-exchange resin. Separate brine
tank.

Model 133210 is the medium size system. The
softener is 32,000 grain capacity. The filter
contains 1.0 cubic feet of carbon. Approximate
flow rate is 6 gallons per minute. Suitable for
homes with 1 to 2 bathrooms.

Model 134815 is the large size system. The
softener is 48,000 grain capacity. The filter
contains 1.5 cubic feet of carbon. Approximate
flow rate is 8 gallons per minute. Suitable for
larger residential and light commercial
applications.

Installation Service

Installation service is available in most of Central
Florida. We obey the "Call Before You Dig" Law.
We can give an accurate quote only after we
inspect the job site. We provide a full tank of
chlorine solution and salt with the installation.
We start up the system.

Maintenance Services

We offer full maintenance services within our
customary service area in East Central Florida.
Contact the store for details.

Support

We offer full technical support after the sale. We
stock parts and supplies for all systems we sell.

Warranty

Installation warranty is 90 days.

Summary of manufacturer's warranty. Retention
tanks, 5 years. Filter and softener tanks 10
years. Automatic backwash valves 5 years.
Chlorine pump 1 year. Flow switch 1 year. All
other equipment as specified by the
manufacturer. Some warranties may vary. See
the manufacturer's warranty for details.

Caution: Warranties may be voided if
equipment is used for irrigation, swimming
pools, pressure cleaning or any other
applications for which equipment is not intended.
Systems and equipment described herein is
intended for potable water treatment on
residential and light commercial applications
only.

Complete terms and conditions are available at
discountwatersupply.com/termsandconditions

Copyright 2003 Discount Water Supply Inc.
All Rights Reserved 0512